

	Core Series				Advanced Series				Slim Series				UST Series				Superior Series				Large Venue Series	
	XJ-V2	XJ-V10X	XJ-V100W	XJ-V110W	XJ-F11X	XJ-F21XN	XJ-F101W	XJ-F211WN	XJ-A142	XJ-A147	XJ-A252	XJ-A257	XJ-UT312WN	XJ-UT352W	XJ-UT352WN	XJ-S400W	XJ-S400WN	XJ-S400U	XJ-S400UN	XJ-L8300HN		
Light Source	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology	Laser & LED Hybrid Technology		
Display Technology	0.55" DLP® Chip	0.55" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.55" DLP® Chip	0.55" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.55" DLP® Chip	0.55" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.65" DLP® Chip	0.66" DLP® Chip		
Colour Reproduction	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)	Full Colour (up to 1.07 billion colours)		
Resolution (Native)	XGA (1024 x 768 pixels)	XGA (1024 x 768 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	XGA (1024 x 768 pixels)	XGA (1024 x 768 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	XGA (1024x768)	XGA (1024x768)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)	WXGA (1280 x 800 pixels)		
Brightness (ANSI Lumens)	3000 Lumens	3300 Lumens	3500 Lumens	3500 Lumens	3000 Lumens	3300 Lumens	3500 Lumens	3500 Lumens	2500 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens	3000 Lumens		
Contrast Ratio	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	1800:1	1800:1	1800:1	1800:1	1800:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1	20,000:1		
Life Expectancy	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours	Up 20,000 Hours		
Country of Origin	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Japan	Taiwan		
Intelligent Brightness Control	Available (Manual)	Available (Manual)	Available (Manual)	Available (Manual)	Available (Auto)	Available (Auto)	Available (Auto)	Available (Auto)	Available (Manual)	Available (Manual)	Available (Manual)	Available (Manual)	Available (Auto/Manual)	Available (Auto/Manual)	Available (Auto/Manual)	Available (Auto/Manual)	Available (Auto/Manual)	Available (Auto/Manual)	Available (Auto/Manual)	-		
Max Signal Resolution	LXGA	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	WUXGA Except Component Signal - Max 1920 x 1080	LXGA	LXGA	LXGA	LXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	WUXGA	HDMI, HDBaseT, 4K UHD VGA - WUXGA	
Lens Zoom (Standard)	1.1x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	1.5x Optical zoom (Manual)	2x Digital zoom (Manual)	2x Digital zoom (Manual)	Available (Manual)	2x Digital zoom (Manual)	Fixed	Fixed	Fixed	1.7x Optical zoom (Manual)	1.7x Optical zoom (Manual)	1.7x Optical zoom (Manual)	1.7x Optical zoom (Manual)	1.5x Optical zoom (Manual)		
Lens Focus	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Electronic	Electronic	Electronic	Electronic	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual		
Keystone Correction	Vertical Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	Vertical Auto: +30° Manual: ±30°	-		
Throw Ratio	1.54 - 1.71 : 1	1.66 to 2.42 : 1	1.32 to 1.93 : 1	1.32 to 1.93 : 1	1.66 to 2.42 : 1	1.66 to 2.42 : 1	1.32-1.93 : 1	1.32-1.93 : 1	1.40-2.8:1	1.40-2.8:1	1.15-2.30 : 1	1.15-2.30 : 1	0.28 : 1	0.28 : 1	0.28 : 1	1.38-2.31:1	1.38-2.31:1	1.32-2.20:1	1.32-2.20:1	1.38 - 2.02 : 1		
Projected Image Size (Diagonally)	30" (0.83m) to 300" (9.4-10.4m) (Aspect ratio 4:3)	30" (0.93m) to 300" (10.1m-14.8m) (Aspect ratio 4:3)	35" (0.93m) to 300" (8.5m-12.5m) (Aspect ratio 16:10)	35" (0.93m) to 300" (8.5m-12.5m) (Aspect ratio 16:10)	30" (0.93m) to 300" (10.1m-14.8m) (Aspect ratio 4:3)	30" (0.93m) to 300" (10.1m-14.8m) (Aspect ratio 4:3)	35" (0.92m) to 300" (8.5m-12.5m) (Aspect ratio 16:10)	35" (0.92m) to 300" (10.1m-14.8m) (Aspect ratio 16:10)	15" (0.84 m) to 300" (8.5m-17.1m) (Aspect ratio 4:3)	15" (0.84 m) to 300" (8.5m-17.1m) (Aspect ratio 4:3)	18" (0.4m-0.9m) to 300" (7.4m-14.9m) (Aspect ratio 16:10)	18" (0.4m-0.9m) to 300" (7.4m-14.9m) (Aspect ratio 16:10)	50" (0.06m) to 110" (0.47m) (Aspect ratio 16:10)	50" (0.06m) to 110" (0.47m) (Aspect ratio 16:10)	50" (0.06m) to 110" (0.47m) (Aspect ratio 16:10)	50" (0.06m) to 110" (0.47m) (Aspect ratio 16:10)	30" (0.77m-1.31m) to 300" (8.6m-14.03m) (Aspect ratio 16:10)	30" (0.77m-1.31m) to 300" (8.6m-14.03m) (Aspect ratio 16:10)	30" (0.77m-1.31m) to 300" (8.6m-14.03m) (Aspect ratio 16:10)	95" (2.89m-4.25m) to 200" (6.09m-8.96m) (Aspect ratio 16:9)		
Projection Distance at 60° Screen	1.79m to 1.99m (Aspect ratio 4:3)	1.95m to 2.87m (Aspect ratio 4:3)	1.64m to 2.42m (Aspect ratio 16:10)	1.64m to 2.42m (Aspect ratio 16:10)	1.95m to 2.87m (Aspect ratio 4:3)	1.95m to 2.87m (Aspect ratio 4:3)	1.64m to 2.42m (Aspect ratio 16:10)	1.64m to 2.42m (Aspect ratio 16:10)	1.7 m to 3.36 m (Aspect ratio 4:3)	1.7 m to 3.4 m (Aspect ratio 4:3)	1.43 m to 2.84 m (Aspect ratio 16:10)	1.43 m to 2.84 m (Aspect ratio 16:10)	0.13m (Aspect ratio 16:10)	0.13m (Aspect ratio 16:10)	0.13m (Aspect ratio 16:10)	1.72m~2.92m (Aspect ratio 16:10)	1.72m~2.92m (Aspect ratio 16:10)	1.64m~2.78m (Aspect ratio 16:10)	1.64m~2.78m (Aspect ratio 16:10)	1.8m-2.7m (Aspect ratio 16:9)		
Projection Distance at 100° Screen	3.7m to 3.41m (Aspect ratio 4:3)	3.33m to 4.85m (Aspect ratio 4:3)	2.81m to 4.11m (Aspect ratio 16:10)	2.81m to 4.11m (Aspect ratio 16:10)	3.33m to 4.85m (Aspect ratio 4:3)	3.33m to 4.85m (Aspect ratio 4:3)	2.81m to 4.11m (Aspect ratio 16:10)	2.81m to 4.11m (Aspect ratio 16:10)	2.81m to 5.61m (Aspect ratio 4:3)	2.8 m to 5.6 m (Aspect ratio 4:3)	2.41 m to 4.75 m (Aspect ratio 16:10)	2.41 m to 4.75 m (Aspect ratio 16:10)	0.40m (Aspect ratio 16:10)	0.40m (Aspect ratio 16:10)	0.40m (Aspect ratio 16:10)	2.94m~4.94m (Aspect ratio 16:10)	2.94m~4.94m (Aspect ratio 16:10)	2.80m~4.70m (Aspect ratio 16:10)	2.80m~4.70m (Aspect ratio 16:10)	3.05m-4.8m (Aspect ratio 16:9)		
Lens Shift	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Vertical: ±60% Horizontal: ±25%		
Dust Resistance Structure	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-	-	-	-	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Computer Input	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	2 x 15-pin RGB mini D-sub (VGA)	2 x 15-pin RGB mini D-sub (VGA)	2 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	2 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	2 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA) * Do not support 4K
Computer Output	-	-	-	-	-	-	-	-	-	-	-	-	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA)	-	1 x 15-pin RGB mini D-sub (VGA)	-	1 x 15-pin RGB mini D-sub (VGA)	1 x 15-pin RGB mini D-sub (VGA) * Do not support 4K		
RS-232C Serial	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	Optional (YK-60)	Optional (YK-60)	Optional (YK-60)	Optional (YK-60)	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	1 x 9-pin mini D-sub	
Digital Input	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	1 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	2 x HDMI Type-A	1x HDMI Type-A (HDMI 2.0 / HDCP 2.2) 1x HDMI Type-A (HDMI 1.4 / HDCP 1.3)	
Composite Video	-	-	-	-	1 x RCA	1 x RCA	1 x RCA	1 x RCA	1 x RCA (via Audio Video Cable for analog input / output)	1 x RCA (via Audio Video Cable for analog input / output)	1 x RCA (via Audio Video Cable for analog input / output)	1 x RCA (via Audio Video Cable for analog input / output)	1 x RCA	1 x RCA	1 x RCA	1 x RCA	1 x RCA	1 x RCA	1 x RCA	-		
Component Video	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	Via RGB input terminal	
Wired LAN Terminal	-	-	-	-	-	1 x RJ45	-	1 x RJ45	-	-	-	-	1 x RJ45	-	1 x RJ45	-	1 x RJ45	-	1 x RJ45	-	1 x RJ45	
HDBase T	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1 x HDBaseT: 1x Audio, 1x Video	
Network Projection	-	-	-	-	-	Yes	-	Yes	-	Yes	-	Yes	Yes	-	Yes	-	Yes	-	Yes	-	Yes	
Wireless Projection	-	-	-	-	-	Optional (YW-41)	-	Optional (YW-41)	-	Yes	-	Yes	Yes (YW-41 Included)	-	Optional (YW-41)	-	Optional (YW-41)	-	Optional (YW-41)	No	No	
USB	1 x Micro USB Type-B: Firmware update only	1 x Micro USB Type-B: Firmware update only	1 x Micro USB Type-B: Firmware update only	1 x Micro USB Type-B: Firmware update only	1 x USB Type-A: Power supply 5V/2A 1 x USB 1.1 Micro-B: Firmware update	a1 x USB Type-A: Power supply 5V/2A Firmware update / logo transfer	1 x USB Type-A: Power supply 5V/2A Firmware update	1 x USB Type-A: Power supply 5V/2A Firmware update	1 x USB 2.0 Micro-B (side): Firmware update / logo transfer	1 x USB 2.0 Micro-B (back): USB display / data transfer 1 x USB 2.0 Micro-B (side): Firmware update / logo transfer	1 x USB 2.0 Micro-B (side): Firmware update / logo transfer	1 x USB 2.0 Micro-B (back): USB display / data transfer 1 x USB 2.0 Micro-B (side): Firmware update / logo transfer	2 x USB 2.0 Type-A: Power supply 5V/2A 1 x USB 2.0 Micro-B: Firmware update / logo transfer	1 x USB 2.0 Type-A: Power supply 5V/2A Firmware update / logo transfer	2 x USB 2.0 Type-A: Power supply 5V/2A 1 x USB 2.0 Micro-B: Firmware update / logo transfer	1 x USB 2.0 Type-A: Power supply 5V/2A Firmware update / logo transfer	2 x USB 2.0 Type-A: Power supply 5V/2A Firmware update / logo transfer	1 x USB 2.0 Type-A: Power supply 5V/2A Firmware update / logo transfer	2 x USB 2.0 Micro-B: Firmware update / logo transfer	1 x USB 2.0 Type-A: Power supply only		
Internal Memory Storage	-	-	-	-	-	-	-	-	-	2Gb	-	2Gb	-	-	-	-	-	-	-	-	-	
Built in Speaker	-	-	-	-	16W	16W	16W	16W	1W	1W	1W	1W	1W	16W	16W	16W	16W	16W	16W	16W	-	
Audio Input	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack 1 x RCA [R/L]	1 x 3.5 mm stereo mini jack RCA x1 [R/L] 1 x 3.5 mm monaural mini jack (for Mic.)*3	1 x 3.5mm Stereo mini jack 1 x RCA [R/L]	1 x 3.5 mm stereo mini jack RCA x1 [R/L] 1 x 3.5 mm monaural mini jack (for Mic.)*3	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	2 x 3.5 mm stereo mini jack RCA x1 [R/L] 1 x 3.5 mm monaural mini jack (for Mic.)	2 x 3.5 mm stereo mini jack RCA x1 [R/L] 1 x 3.5 mm monaural mini jack (for Mic.)	2 x 3.5 mm stereo mini jack RCA x1 [R/L] 1 x 3.5 mm monaural mini jack (for Mic.)	1 x 3.5 mm stereo mini jack RCA x1 [R/L]	2 x 3.5 mm stereo mini jack RCA x1 [R/L]	1 x 3.5 mm stereo mini jack RCA x1 [R/L]	2 x 3.5 mm stereo mini jack RCA x1 [R/L]	1 x 3.5 mm stereo mini jack RCA x1 [R/L]	-	
Audio Output	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack (Used for both video and audio input/output)	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	1 x 3.5mm Stereo mini jack	
Time To Max Brightness	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	8 sec	8 sec	8 sec	8 sec	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	5 sec	30 sec	
Instant Off	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Noise Level	29dB (Eco Mode) 37dB (Normal)	29dB (Eco Mode) 37dB (Normal)	29dB (Eco Mode) 35dB (Normal)	29dB (Eco Mode) 35dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	29dB (Eco Mode) 36.5dB (Normal)	28dB (Eco Mode) 37dB (Normal)	A28dB (Eco Mode) 36dB (Normal)	28dB (Eco Mode) 37dB (Normal)	28dB (Eco Mode) 36dB (Normal)	28dB (Eco Mode) 36dB (Normal)	28dB (Eco Mode) 36dB (Normal)	28dB (Eco Mode) 36dB (Normal)	28dB (Eco Mode) 39dB (Normal)	36dB (Eco Mode) 39dB (Normal)	
ES Solution	-	-	-	-	ES Standard	ES Network	ES Standard	ES Network	-	-	-	-	ES Network	ES Standard	ES Network	ES Standard	ES Network	ES Standard	ES Network	ES Standard	-	
Security Compatibility	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	Kensington Compatible, Security Bar, Power On Password	
Power Consumption	Eco Lv1: 130W Eco Lv5: 75W Normal: 140W	Eco Lv1: 75W Eco Lv7: 145W Normal: 155W	Eco Lv1: 60W Eco Lv7: 125W Normal: 135W	Eco Lv1: 80W Eco Lv7: 155W Normal: 165W	Eco Lv1: 80W Eco Lv7: 160W Normal: 170W	Eco Lv1: 80W Eco Lv7: 165W Normal: 175W	Eco Lv1: 85W Eco Lv7: 165W Normal: 175W	Eco Lv1: 85W Eco Lv7: 165W Normal: 175W	Eco Lv1: 70W Eco Lv5: 115W Normal: 125W	Eco Lv1: 70W Eco Lv5: 115W Normal: 125W	Eco Lv1: 75W Eco Lv5: 120W Normal: 135W	Eco Lv1: 75W Eco Lv5: 120W Normal: 135W	Eco Lv1: 90W Eco Lv7: 185W Normal: 170W	Eco Lv1: 105W Eco Lv7: 215W Normal: 200W	Eco Lv1: 105W Eco Lv7: 215W Normal: 200W	Eco Lv1: 120W Eco Lv7: 210W Normal: 225W	Eco Lv1: 135W Eco Lv7: 215W Normal: 200W	Eco Lv1: 135W Eco Lv7: 215W Normal: 200W	Eco Lv1: 135W Eco Lv7: 215W Normal: 200W			